



WL100

Convenient water dispensing unit for budget applications

Economical solution for perfectly chilled and hot water

A great value dispenser, supplying refreshing drinking water for the workplace without the hassle of bottles. The WL100 is the ideal solution for basic hydration needs at a competitive price.

Advanced technology

The WL100 features two core technologies:



High performance filtration

Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



BioCote®* product protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



Water that doesn't cost the earth

The WL100 is Energy Star certified, BPA free, and reduces plastic bottle contribution to landfills.

*BioCote® silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote® does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

Ergonomic design with simple buttons and icons for easy dispensing operation

BPA free and better for the environment

Sleep mode to conserve energy

Recessed faucet to help prevent contamination

Generous drip tray capacity to collect accidental spillage

Key dispenser surfaces are protected by BioCote® product preservation technology against odor and stain causing microbes

Easy connection to the existing mains water supply

Water options

cold

hot



Number of users: 10-20

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding

13.6" (W) x 40.2" (H) x 14.40" (D)

Countertop

13.6" (W) x 17.7" (H) x 14.40" (D)

Dispensing area height

8.7"

Weight (Hot and cold models)

Freestanding: ~61.7lbs

Countertop: ~50.7lbs

Standard filtration recommended

Carbon block

Storage capacity

Cold tank: 2 liters

Hot tank 1.6 liters

Drip tray capacity

1.3 liters

Compressor

110V/120V/60Hz

Water temperatures settings

Cold: 37°-54°F

Hot: 187°F

Contact us today

Waterlogic Commercial Products

www.waterlogicdealers.com

(800) 288-1891

customerservice@waterlogicausa.com

3175 Bass Pro Drive
Grapevine, TX 76051

Tested and certified

